

# ZAP Controls

## Loop Detectors 1102/1100-CC/1104-CC-120/240

### 1102

#### Description:

The 1102 is a plug in single magnetic loop detector used for indicating the presence or passage of vehicles. A system consists of an inductive loop (not provided) and the 1102 Loop detector.



### 1102

**Wiring requirements:** 14-20 AWG

**Power requirement:** None

**Mounting type:** Plug in

**Dimensions: 1102**  
Height: 3.5"  
Width: 3.5"  
Depth: 1"

**Works with:**  
All commercial ZAP Controllers

**Operating temperature:**  
-13 deg F to + 149 deg F

### 1100-CC

The 1100-CC is a wall mount single magnetic loop detector used for indicating the presence or passage of vehicles. A system consists of an inductive loop (not provided) and the 1100 Loop detector.



### 1100-CC/1104-CC-120/240

**Wiring requirements:** 14-20 AWG

**Power requirement:**  
1100-CC 24VDC  
1104-CC-120 120VAC  
1104-CC-240 240VAC

**Case dimensions:**  
Height: 6.693"  
Width: 5.512"  
Depth: 5.315"

**Mounting type:**  
Wall mount, Loop detector mounts on din rail.

**Works with:**  
All commercial ZAP Controllers

### 1104-CC-120

### 1104-CC-240

The 1104-CC is a wall mount twin magnetic loop detector used for indicating the presence or passage of vehicles. A system consists of an inductive loop (not provided) and the 1104 loop detector.



**Operating temperature:**  
-13 deg F to + 149 deg F

ZAP Controls  
Loop Detectors 1102/1100-CC/1104-CC-120/240

1100 1102 1104 USA

### ZAP Series 3 Simply Logical

ZAP Controls  
100 Waterloo Blvd. Anglesey Business Park, Littleworth Road, Cannock, Staffordshire, England  
UK Office Number 011-44-154-387-9444 sales@zap-uk.com  
USA Contact 931-510-4432 sales@zap-america.com  
USA Tech Support 931-510-4432 via telephone or text  
Online www.zap-uk.com