ZAP Controls

Forklift Radio Control Transmitters

4500-50

Description:

Forklift mounted transmitter. The transmitter features a heavy duty die-cast aluminum housing in a high visibility orange color and are rated for indoor use. The transmitter is designed to permanently mount to the forklift, eliminating the constant loss associated with handheld transmitters. The units permanently wire to the forklift battery system and offer a voltage range of 12 to 72 volts dc. Models are available in 1, 2, 4, and 6 channels.

ZAP part numbers: 4501-50 1 button

4502-50 2 button 4504-50 4 button 4506-50 6 button

Case dimensions:

4-1/2" Length: w/ antenna: 6-3/4" Width: 2-1/2" 2-3/16" Depth:

Works with: 840 Receiver

Battery: None

Frequency: 433.92 Mhz.

Operating temperature:

-13 deg F to + 149 deg F



4500-66 Description:

Forklift mounted transmitter. The transmitter features a heavy duty die-cast aluminum housing in a high visibility orange color and are rated for outdoor use. The transmitter is designed to permanently mount to the forklift, eliminating the constant loss associated with handheld transmitters. The units permanently wire to the forklift battery system and offer a voltage range of 12 to 72 volts dc. Models are available in 1, 2, 4, and 6 channels.

ZAP part numbers: 1 button 4501-66 4502-66 2 button

4504-66 4 button 4506-66 6 button

Case Dimensions:

Length: 4-1/2" w/ antenna: 6-3/4" Width: 2-1/2" Depth: 2-3/16"

Works with: 840 Receiver

Battery: None

Frequency: 433.92 Mhz.

Operating temperature:

-13 deg F to + 149 deg F



ZAP Series 3 Simply Logical

ZAP Controls

500-50 4500-66 USA

UK Office Number USA Contact USA Tech Support

011-44-154-387-9444 931-510-4432 931-510-4432 www.zap-uk.com

100 Waterloo Blvd. Anglesey Business Park, Littleworth Road, Cannock, Staffordshire, England sales@zap-uk.com sales@zap-america.com via telephone or text